

LPS SERIES-Solar Power

LPS2-500 (2V518AH)

Specification

Nominal Voltage	2V
Nominal Capacity(100HR)	518.0AH
Dimension	Length 210±2mm (8.27 inches)
	Width 175±2mm (6.89 inches)
	Container Height 330±2mm (12.99 inches)
	Total Height (with Terminal) 350±2mm (13.78 inches)
Approx Weight	Approx 27.0 Kg (59.5 lbs)
Terminal	T11
Container Material	ABS
Rated Capacity	518.0 AH/5.18A (100hr, 1.80V/cell, 25°C/77°F)
	482.0 AH/24.1A (20hr, 1.80V/cell, 25°C/77°F)
	450.0 AH/45.0A (10hr, 1.80V/cell, 25°C/77°F)
	395.5AH/79.1A (5hr, 1.75V/cell, 25°C/77°F)
	264.6 AH/264.6A (1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	3600A (5s)
Internal Resistance	Approx 0.65mΩ
Operating Temp. Range	Discharge : -15~50°C (5~122°F)
	Charge : 0~40°C (32~104°F)
	Storage : -15~40°C (5~104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)
Cycle Use	Initial Charging Current less than 135.0A. Voltage 2.4V~2.5V at 25°C(77°F)Temp. Coefficient -5mV/°C
Standby Use	No limit on Initial Charging Current Voltage 2.25V~2.3V at 25°C(77°F)Temp. Coefficient -3mV/°C
Capacity affected by Temperature	40°C (104°F) 103%
	25°C (77°F) 100%
	0°C (32°F) 86%
Self Discharge	TRV LPS series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.



Applications

- ◆ Green energy systems
- ◆ Communication systems

TRV battery is green battery, focus on the Environmental protection and Ecological protection, which well connect human being and environment into harmony. Continuous power supply for people, and being benign cycle back to the green environment.



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	30min	45min	1h	2h	3h	4h	5h	8h	10h	20h	48h	100h
1.85V/cell	330.3	262.1	217.5	135.7	105.0	86.5	73.6	52.4	43.6	23.2	10.3	5.07
1.80V/cell	354.4	275.7	231.1	143.3	110.0	90.3	76.7	54.1	45.0	24.1	10.5	5.18
1.75V/cell	375.3	289.9	241.1	148.7	113.7	93.4	79.1	55.1	45.7	24.2	10.6	5.22
1.70V/cell	393.7	300.8	249.6	153.2	116.7	95.4	80.4	56.0	46.2	24.5	10.8	5.29
1.65V/cell	413.0	314.0	258.5	156.8	119.6	97.5	82.2	56.8	46.8	24.8	10.9	5.35
1.60V/cell	427.1	322.3	264.6	160.2	121.7	98.9	83.4	57.5	47.5	25.1	11.0	5.41

Constant Power Discharge (Watts) at 25 °C (77°F)

F.V/Time	30min	45min	1h	2h	3h	4h	5h	8h	10h	20h	48h	100h
1.85V/cell	631.2	503.9	420.8	263.9	205.2	169.6	145.0	104.0	86.6	46.3	20.5	10.1
1.80V/cell	671.8	526.6	444.5	277.4	213.9	176.6	150.5	107.0	89.4	47.9	20.8	10.3
1.75V/cell	706.0	550.5	461.8	286.8	220.6	181.9	154.6	108.8	90.6	48.0	21.1	10.4
1.70V/cell	734.5	567.3	475.4	294.2	225.5	185.2	156.8	110.3	91.5	48.6	21.3	10.5
1.65V/cell	764.8	588.7	489.7	299.8	230.0	188.5	159.6	111.6	92.7	49.2	21.6	10.6
1.60V/cell	782.9	598.6	497.7	304.4	232.9	190.3	161.2	112.9	93.8	49.7	21.8	10.7





Specifications subject to change without notice.



Dimensions

T11 Terminal

Unit: mm [inches]



Discharge Characteristics

