



Higher Durability

The multi-busbar design can decrease the risk of the cell micro- cracks and fingers broken.



High Power Density

High conversion efficiency and more power output persquare meter,by lower series resistance and improved light harvesting.



PID Resistant

Tested in accordance to the standard IEC 62804, our PV modules have demonstrated resistance against PID (Potential Induced Degradation), which translates to security for your investment.



Bigger Cells with better performance

A slight increase of the size of our cells, Boosts the performance of the newest modules by six percent on average.

• 25-year linear power output warranty



Comprehensive Certificates

- IEC61215, IEC61730
- ISO9001:2015 Quality management systems









■ MECHANICAL DIAGRAMS

760 760 30 25 092 25 730 8-9*14 Installation holes

SPECIFICATIONS

Weight	11.3kg
Dimensions	530mm*760mm*30mm
Cell Amount	4*8 or 4*16pcs
Maximum Syste	m Voltage 1000V
Output Tolerand	e ± 3%
Junction Box	IP67
Cable	2.5mm²/700mm
Connector	MC4 Compatible
Frame	Aluminum Alloy
Operating Temp	erature -40°C~+85°C
Wind Load/Snov	v Load 2400pa/5400pa

ELECTRICAL PARAMETERS AT STC

Module Type	SPD240P-32M
Maximum Power (Pmax/W)	240
Open Circuit Voltage(Voc/V)	21.80
Short Circuit Current(Isc/A)	13.95
Maximun Power Voltage(Vmp/V)	18.24
Maximum Power Current(Imp/A)	13.16
Module Efficiency(%)	20.70

^{*} Under Standard Test Conditions (STC) of irradiance of 1000 W/m², spectrum AM 1.5 and cell temperature of 25°C.

TEMPERATURE CHARACTERISTICS

NOCT	45±2°C	Temp Coefficient of Isc	+0.046%/°C
Temp Coefficient of Voc ■ PACKING CONFIGURE	-0.275%/°C RATION	Temp Coefficient of Pmax	-0.350%/°C
Modules/Pallet	2 or 36 Pieces	Modules/40HQ'Container	1660 or 1620 Pieces